

CO-sinusUPS-400W-WM

Pure sine wave inveter (400W) designed for wall mounting




■ Features:

- Easy user interface
- Compact size
- Low price
- Designed for wall mounting



ELECTRICAL SPECIFICATION

MODEL	CO-sinusUPS-400W-WM
OUTPUT	
<i>Rated Power</i>	400W
<i>Output voltage range (AC mode)</i>	210 ÷ 235VAC (±7VAC)
<i>Output voltage (Battery mode)</i>	190 ÷ 255VAC (±5VAC)
<i>Output frequency (Battery mode)</i>	50Hz
<i>Output waveform</i>	Pure sine wave
<i>Transfer time</i>	< 10ms
INPUT	
<i>Voltage Range</i>	147 ÷ 275VAC (±5VAC)
<i>Input frequency</i>	47 ÷ 65Hz
BATTERY	
<i>Charging current (max.)</i>	5A
<i>Type and capacity of battery</i>	12V GEL / AGM / WET; 26-100Ah
WORKING ENVIRONMENT	
<i>Working Temperature</i>	0°C ÷ 40°C
<i>Working Humidity</i>	10 ÷ 90% RH non-condensing
<i>Noise level</i>	< 40dB (1m)
OTHERS	
<i>Wire input</i>	Electric plug - SCHUKO - H05VV-F AWG18 (3x0.5mm ²) – 1000mm
<i>Wire output</i>	Red – 650mm, black – 710mm; 8AWG (8mm ²); Ring terminal - M8
<i>Weight and dimensions</i>	5.9 kg; 267 x 267 x 115mm (L x W x H)
<i>Weight and box dimension</i>	6.5 kg; 345 x 330 x 190 mm (L x W x H)
<i>EAN code</i>	 51190213541258471

CO-sinusUPS-400W-WM

Pure sine wave inveter (400W) designed for wall mounting



MECHANICAL SPECIFICATION

