

CO-sinusUPS-600W-LCD

Inverter with UPS function (600VA / 500W)



■ Features:

- Friendly interface
- Compact size
- Low price



ELECTRICAL SPECIFICATION

MODEL	CO-sinusUPS-600W-LCD
OUTPUT	
Rated Power	500W (600VA)
Output Voltage Range (inverter mode)	150 ÷ 255VAC (±5VAC)
Output Voltage Range (bypass mode)	203 ÷ 238VAC (±5VAC)
Frequency (battery mode)	50Hz ± 0.1Hz
Voltage waveform	True sinus
Transfer time	< 10ms
INPUT	
Input Voltage Range (inverter mode)	100 ÷ 264VAC (±5VAC)
Input Voltage Range (bypass mode)	203 ÷ 238VAC (±5VAC)
Frequency Range	45 ÷ 65Hz
BATTERIES	
CHARGING CURRENT (MAX.)	10A/20A/Max.
Type and Capacity Of Batteries	GEL / AGM / ACID; 12V/55-200Ah
Power consumption without load	3.4A
WORKING ENVIRONMENT	
Working Temperature	0°C ÷ 40°C
Working Humidity	20 ÷ 90% RH non-condensing
Noise Level	< 40dB (1m)
OTHERS	
Wire input	Electric plug - SCHUKO - H05VV-F AWG14 (3x1mm ²) – 850mm
Wire output	Red – 560mm, black – 670mm; 7AWG (10mm ²); Ring terminal - M8
Weight and dimensions	9.6 kg; 300 x 255 x 125mm (L x W x H)
Weight and box dimension	10 kg; 340 x 315 x 210mm (L x W x H)
EAN Code	 5190213541240861

CO-sinusUPS-600W-LCD

Inverter with UPS function (600VA / 500W)



MECHANICAL SPECIFICATION

